

SUPrema

BioStation T2

Fingerprint IP Access Terminal with Face Detection



BioStation T2 | The new BioStation T2 blends loads of innovative features with Suprema's sophisticated fingerprint recognition technology. Its powerful dual-CPU engine ensures seamless operation and internal camera captures face image logs (snap shots) for extra level of security. Sealed in a flat-panel front glass and refined dimensions, it provides intuitive and aesthetic GUI on easy-to-use touchscreen LCD. In addition to its extensive communication interfaces, BioStation T2 also supports embedded web server which provides convenience system management over its IP-based access control system.










SUPREMA BioStation T2

Fingerprint IP Access Terminal with Face Detection



Features

- 
Intuitive Touchscreen GUI
 5" touchscreen LCD with easy-to-use GUI
- 
Face Detection Technology
 Camera for face image capture
- 
Embedded Web Server
 Preloaded with BioStar Lite embedded web server
- 
Ultra Performance
 1:3,000 matches in one second, 200k users/1 million logs
- 
Versatile Interfaces
 PoE, WiFi, TCP/IP, RS485/232, Wiegand, relay
- 
Video Phone
 IP based video and audio interface or analog video phone
- 
RF Card Options
 EM, Mifare/DesFire

Intuitive Touchscreen GUI of BioStation T2




Specifications

CPU	667MHz RISC, 533MHz DSP
Memory	1GB flash, 256MB RAM
LCD	5.0 inch WVGA touchscreen
Fingerprint Sensor	Optical
Camera	Face detection & videophone
RF Card Options	EM, Mifare / DesFire
Template Capacity	400,000 (1:1), 20,000 (1:N)
Max User	200,000
Log Capacity	Fingerprint: 1,000,000 / Image: 5,000
PoE	Yes
Interfaces	Wireless LAN(optional), TCP/IP, Wiegand 2ch RS485, RS232, 4 x TTL I/O, 2 x Relay USB (Host & Slave), SD card slot
Tamper	Switch
Sound	16 bit Hi-Fi voice & sound indication
Operating Temp.	- 20°C ~ 50°C
Operating Voltage	12vDC
Dimensions (mm)	155(W) x 155(H) x 40(D)


Secure I/O

- External Relay unit for secure door control and I/O expansion
- Encrypted communication for enhanced security

- * 16MHz 8 bit microprocessor
- * 4 digital inputs and 2 relay outputs
- * Dimension :
143 x 82 x 35 mm (W x H x D)



System Configuration



Suprema Inc.

16F Parkview Tower, Jeongja, Bundang, Seongnam, Gyeonggi, 463-863 Korea

Tel : +82-31-783-4502, Fax : +82-31-783-4503

E-mail : sales@supremainc.com Homepage : www.supremainc.com

©2011 Suprema, Inc. Suprema and identifying product names and numbers herein are registered trademarks of Suprema, Inc. All non-Suprema brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice.

